# PT1RSE

## TOUCH SCREEN LCD DISPLAY

| | |
|---|---|
| **Panel Type** | 10.4” TFT Active Matrix Panel |
| **Max. Resolution** | 800×600 SVGA |
| **Pixel Pitch** | 0.264 (H) × 0.264 (V) |
| **Contrast Ratio** | 500:1 |
| **Brightness** | 230 cd/m2 |
| **Display Area** | 211.2 × 158.4 mm |
| **Response Time** | 35 ms (Typ.) |
| **Display Colors** | 262K |
| **Viewing Angle** | 120°(H)/100°(V) |
| **Signal Connector** | VGA |
| **VGA Input Signal** | RGB Analog 0.7V Peak to Peak |
| **OSD Control** | Power Switch, Menu, Select (+, -), Auto |
| **Operation Temperature** | 0° ~ 50° C |
| **Storage Temperature** | -20° ~ 60° C |
| **Power Consumption** | 25 W |
| **Power Supply** | External Power Adapter |
| **Safely & EMI** | CE, FCC, TUV-GS, UL Compliant |
| **Touch screen** | Resistive; RS232 |
| **Mounting** | VESA 75 mm; Table Mount |
| **Dimension** | (With Stand) 274.62 x 245.23 x 153.54(mm)<br>10.82” x 9.65” x 6.05”<br>(Without Stand) 274.62 x 201.62 x 48.95 (mm)<br>10.82” x 7.94” x 1.93” |
| **Weight** | 4.75 lbs (2.1 kg) |

ACCUVIEW INC•
Tel: 800.275.4255 Fax: 201.440.5655 Address: 40C Cotters Lane, Suite F, East Brunswick NJ 08816 Email: sales@accuview.com
*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 Accuview Inc. All rights reserved.

**WWW.ACCUVIEW.COM**

Rev. 07/12